



Standalone Access Control System



Real Time **TD1D** FINGERPRINT READER

Specifications :

FINGERPRINT CAPACITY	: 500
PASSWORD CAPACITY	: 500
PIN READER	: 4~6 Digit
SENSOR	: 500 DPI
IDENTIFY MODE	: Fingerprint & Password
WORKING VOLTAGE	: DC12V
WORKING TEMPERATURE	: -100C~+500C
WORKING HUMIDITY(RH)	: 20%~80%
WIRING CONNECTION	: Relay Output, Exit Button, Alarm, Wiegand Output
FAR/ FRR	: 0.001/1(%)
INTERLOCKING	: Yes

Standalone Access Control System



Realtime TD1D

Standalone Access Control System



Finger



RF Card



Personal
Identity Number



Access
Control

Specifications

Fingerprint capacity	500
Card capacity	500
Password capacity	500
PIN Reader	4~6 Digit
Sensor	500 DPI
Identify mode	Fingerprint, card, Password
Card Reader	Standard 26 bit
Read Range	1~5 CM
Working voltage	DC12V
Working temper ature	-10℃~ +50℃
Working humidity(RH)	20% ~ 80%
Wiring Connection	Relay Output, Exit Button, Alarm, Wiegand Output
FAR/ FRR	0.001/1(%)
Interlocking	Yes