



SPEEDFACE - 4



Face



Touch Screen



RFID



Live Body Detection



LAN



USB



Access Control

Facial Attendance and Access Control

Storage Capacity

Face ID Capacity	10,000
Max Users	10,000
Card Capacity	10,000
Log Capacity	50,000



Features

High Speed and accurate verification

World class face algorithm for identification

Access control to secure your premises

With and without face mask detection options

Dual Camera for live body sensing & observation

Camera support low light and normal light

4 inch touch display with easy handling features

SpeedFace - 4

Communication Interface

Communication

WIFI, TCP/IP, USB

Biometric

Push Data	YES
Remote firmware update	YES
FAR	0.001%
Accuracy ratio	99.27%
Processor	Dual Core ARM Cortex-A7 @900MHz
OS	Linux
Verification time	<=1 second
Mifare Card	Yes



Auto Focus



low light Verification



Long Distance Verification

Audio/Visual

LCD	4" IPS touch screen display
Shutter type	Electronic Rolling Shutter
Language	English

Software

Web & Cloud

Access control

Relay	YES
Wiegand In/out	YES
Live Detection	YES
Storage	512 MB RAM, 4GB ROM



Time Attendance



Access Control



Employee Self Service



Mobile App

Power & Environment

Operating Temperature	0°C ~ 50°C
Working Humidity	10% ~ 90%
Power	12V DC / 2A
Dimension	166 x 80 x 21 mm

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by



www.biomaxsecurity.com

Connect with us on

BiomaxOfficial

biomaxsecurity

BioMax Security

BioMax Access Control