

Products

Home / HD-TVI Camera / Entry Level Series / PT-HTD700E-IP

Performance Personified

Robustly built of our products keeps the downtime at bay. Thus assuring a flawless performance by keeping you secure all the time.



PT-HTD700E-IP

2 MP IR Turret Camera

KEY FEATURES

- 2 MP high performance CMOS
- 1920 x 1080 resolution
- 2.8 mm, 3.6 mm fixed lens
- Up to 20 m IR distance
- OSD menu, DNR, DWDR
- Analog HD output
- Up the coax (PRAMA)

[ADD TO COMPARE](#)

CAMERA

Image Sensor	:	2 MP CMOS image sensor
Signal System	:	PAL/NTSC
Frame Rate	:	"PAL: 1080p@25fps NTSC: 1080p@30fps
Resolution	:	1920 (H) x 1080 (V)
Min. illumination	:	0.02 Lux @ (F1.2,AGC ON), 0 Lux with IR
Shutter Time	:	"PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Lens	:	2.8 mm, 3.6 mm fixed lens
Horizontal Field of View	:	103° (2.8 mm), 82.2° (3.6 mm)
Lens Mount	:	M12
Day & Night	:	IR cut filter
Angle Adjustment	:	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°



WDR (Wide Dynamic Range) : DWDR

MENU

Image Mode : STD/HIGH-SAT
AGC : Support
Day/Night Mode : Smart/color/BW(Black and White)
Backlight Compensation : Support
DWDR : Support
Language : English
Functions : Brightness, Sharpness, DNR, Mirror

INTERFACE

Video Output : 1 HD analog output

GENERAL

Operating Conditions : -40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)
Power Supply : 12 VDC±15%
Power Consumption : Max. 4 W
Material : Plastic
IR Range : Up to 20 m
Dimension : Ø 89.9 mm x 71.3 mm (Ø 3.54inch x 2.81inch)
Weight : Approx. 120 g (0.26 lb.)





PT-HTD110E-IP

2 MP Indoor IR
Bullet Camera

 **ADD TO COMPARE**

